



**Declaration of Conformity – Number 038/08**

***Hamberger Flooring GmbH & Co. KG, PO Box 100353,  
D-83003 Rosenheim***

**hereby declare that the construction product**

**HARO Parquet 2500 12mm**

produced in the Rosenheim plant,

**for internal installation other than high moisture content  
areas in the building industry, over subfloor installation,  
with the following features/properties<sup>\*)</sup>:**

<b>Thickness:</b>	<i>12 mm</i>
<b>Density:</b>	<i>&gt; 500 kg/m<sup>3</sup></i>
<b>Fire protection:</b>	<i>D<sub>FI</sub> - s1</i>
<b>Formaldehyde class:</b>	<i>E1</i>
<b>Thermal resistance</b>	<i>0.098 m<sup>2</sup>K/W</i>

**corresponds with EN 14342, Annex ZA**

**Hamberger Flooring GmbH & Co. KG**

**Peter Hamberger**

**Stephanskirchen 30 October 2008**

<sup>\*)</sup> see back side

Evidence of conformity of **reaction to fire with DIN EN 14 342**  
chart 1 (CWFT).

Evidence of conformity of **formaldehyde release with DIN EN 717-1** established by:

Fraunhofer-Institute for Wood Research  
Wilhelm-Klauditz-Institut WKI

Bienroder Weg 54 E · D-38108 Braunschweig, Germany

ID No. 0765

Further applicable standards:

- **DIN EN 12524** Building materials and products; Hygrothermal properties; Tabulated design values