



Declaration of Conformity – Number 036/08

***Hamberger Flooring GmbH & Co. KG, PO Box 100353,
D-83003 Rosenheim***

hereby declare that the construction product

HARO Parquet 4000 13.5mm

produced in the Rosenheim plant,

**for internal installation other than high moisture content
areas in the building industry, over subfloor installation,
with the following features/properties*):**

Thickness:	<i>13.5 mm</i>
Density:	<i>> 500 kg/m³</i>
Fire protection:	<i>≥ D_{FI}- s1^{**})</i>
Formaldehyde class:	<i>E1</i>
Thermal resistance	<i>0.11 m²K/W</i>

corresponds with EN 14342, Annex ZA

Hamberger Flooring GmbH & Co. KG

Peter Hamberger

Stephanskirchen 31 October 2008

*) see back side:

****)** **Reaction to fire** (individual verification)
C_{FI}-s1 in the wood species "Achateiche" (oak), varnished.

Evidence of conformity of **reaction to fire with DIN EN 14 342**
chart 1 (CWFT).

Evidence of conformity of **reaction to fire with DIN EN 13 501-1**
established by:

MPA Dresden GmbH
Fuchsmühlenweg 6F * 09599 Freiberg
Ident-No. 0767

Evidence of conformity of **formaldehyde release with DIN EN**
717-1 established by:

Fraunhofer-Institute for Wood Research
Wilhelm-Klauditz-Institut WKI
Bienroder Weg 54 E * D-38108 Braunschweig, Germany
ID No. 0765

Further applicable standards:

- **DIN EN 12524** Building materials and products; Hygrothermal properties; Tabulated design values