



Declaration of Conformity – Number 028/08

***Hamberger Flooring GmbH & Co. KG, PO Box 100353,
D-83003 Rosenheim***

hereby declare that the construction product

HARO Tritten Laminat Floor 250

produced in the Rosenheim plant,

for use in the building industry, for the interior use as non-load bearing building component in dry areas with the following features/properties*):

| | |
|------------------------------|-------------------------------|
| Thickness: | <i>9.6 mm</i> |
| Substance: | <i>9.3 kg/m²</i> |
| Fire protection: | <i>C_{fl} - s1</i> |
| Formaldehyde class: | <i>E1</i> |
| Slip resistance: | <i>NPD</i> |
| Thermal resistance | <i>0.069 m²K/W</i> |
| Antistatic behaviour: | <i>< 2kV</i> |

corresponds with EN 14041, Annex ZA

Hamberger Flooring GmbH & Co. KG

Peter Hamberger

Stephanskirchen, 03 November 2008

***) see back side:**

Evidence of conformity of **reaction to fire with DIN EN 13 501-1** established by:

MPA Stuttgart · Otto-Graf-Institute
Materials Testing Institute · University of Stuttgart
Fire Protection Dept. · Fire Classification of Building Materials
Pfaffenwaldring 4 · D-70569 Stuttgart, Germany
ID No. 0672

Evidence of conformity of **formaldehyde release with DIN EN 717-1** established by:

Fraunhofer-Institute for Wood Research
Wilhelm-Klauditz-Institut (WKI)
Bienroder Weg 54 E · D-38108 Braunschweig, Germany
ID No. 0765

Further applicable standards:

- **DIN EN 13893** Resilient, laminate and textile floor coverings; Measurement of dynamic coefficient of friction on dry floor surfaces
- **DIN EN 12524** Building materials and products; Hygrothermal properties; Tabulated design values
- **DIN EN 1815** Resilient and textile floor coverings; Assessment of static electrical propensity